

## MINI Fittings

### LC SERIES



#### Product features

- The compact fittings used to the pneumatic tube system
- The volume is 40% smaller than the standard pneumatic fittings
- The small and oval sleeve is easy to push in and pull out the tube

#### Speciality

Fluid	Air /no other gases or liquids)
Operating Pressure	0~1.0 MPa ( 150psi )
Negative Pressure	-100Kpa(-29.5 in Hg)
Operating Temperature	-60°C (32-140°F)
Applicable Tube	PU Polyurethane and Nylon

#### Ordering Code

**PC - 06 - 01 - C**

Compact one touch fitting	Tube Dia Code    Size 03    φ03 04    φ04 06    φ06	Thread Size Metric Thread Code    Size M3    M3X0.5 M5    M3X0.8 M6    M6X1.0  R (PT) Thread Code    Size 01    R1/8	Compact Nickel

Note: we can make other smaller thread.

#### Dimension

MODEL	φD	M	L	L1	L2	
LC0320-M3	3X2	M3X0.5	10	2.5	5	5
LC0320-M5	3X2	M5X0.8	11.5	3.5	5	7
LC0425-M3	4X2.5	M3X0.5	10	2.5	5	5
LC0425-M5	4X2.5	M5X0.8	11.5	3.5	5	7
LC0640-M5	6X4	M5X0.8	13.5	3.5	7	7

